



MATERIAL:
 Insulator: NYLON66 UL94V-0+GF Black
 Contact: Brass Gold 2u" over nickel plated

- NOTES:**
- 1.ASSEMBLY TOTAL LENGTH 57.0±2.0
 - 2.WATERPROOF RATE:IP68
 - 3.UV RESIST

ORDERING CODE

LJ125 XXX AS - RM - XX - D 08

PIN OPTION
 180=2~3P (10A)
 100=4~6P (5A)
 210=2+5P (7A+3A)
 075=7~18P (2A)

ASSEMBLY TYPE

Cable ID OPTION
 08=Ø8.0 10=Ø10.0
 D=W/DUST COVER
 N=W/O DUST COVER

NO. OF CONTACTS
 RM=MALE PIN
 PF=FEMALE PIN

CIRCUITS	2P	3P	4P	5P	6P	2+5P	18P
ARRANGEMENT OF CONTACT							
SERIES	LJ125180-02	LJ125180-03	LJ125100-04	LJ125100-05	LJ125100-06	LJ125210-07	LJ125075-18

詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD.	TITLE	QUICK PULL IN-OUT WATER PROOF MALE PIN & FEMALE PIN ASS'Y ILLUSTRATION	TOLERANCE	DRAWN	許建華	DATE	2011.05.25		
	PART NO.	LJ125XXXAS-RM-XX-D08	DIM.	CHECK		DATE			
	DWG.NO.	LJ125XXXAS-RM-XX-D08	.0 ±0.30	APPROVE		DATE			
			.00 ±0.20	SCALE		UNIT	mm	REV.	01